



Graceful, Solid...

VISION
LINE

15" / 17" / 19" LCD Monitor



KS-ML1520

- 15" Multi-inputs LCD monitor
- Fast response time at 16ms
- High contract ratio at 500:1
- High brightness at 250 cd/m²
- Selectable power on source : AV1, PC, S-Video
- Support multiple language selections
- Selectable color temperature under PC mode
- Sleep timer definable for users
- 2D comb filter and 2D de-interlace



KS-ML1720 / KS-ML1910

- 17" Multi-inputs LCD monitor
- Fast response time at 8ms (ML1720) / 6ms (ML1920)
- High contract ratio at 500:1(ML1720) / 700:1(ML1920)
- High brightness at 290 cd/m²(MI1720) / 300 cd/m²(MI1920)
- Selectable power on source : AV1, PC, S-Video
- Support multiple language selections
- Selectable color temperature under PC mode
- Sleep timer definable for users
- 2D comb filter and 2D de-interlace



Model	15" LCD	17" LCD	19" LCD
Front Control	Menu, VOL-, VOL+, Source, Power (Remote Controller Optional)	Menu, VOL-, VOL+, Source, Power (Remote Controller Optional)	Menu, VOL-, VOL+, Source, Power (Remote Controller Optional)
Display Resolution (Dot)	640x480@60/72/75, 800x600@56/60/72/75, 1024x768@60/70/75	640x480@60/72/75, 800x600@56/60/72/75, 1024x768@60/70/75 1280 x 1024@60/75	640x480@60/72/75, 800x600@56/60/72/75, 1024x768@60/70/75 1280 x 1024@60/75
Active Area (mm)	304.128(H)x228.096(V)	337.920(H)x270.336(V)	376.32(H)x301.06(V)
Dot Pitch (mm)	0.297x0.297mm	0.264x0.264mm	0.294x0.294mm
LCD Profile Ratio	4:3	5:4	5:4
Display Color	16.2M	16.2M	16.2M
Brightness (Central)	250cd/m ²	290cd/m ²	300cd/m ²
Contrast Ratio	500:1	500:1	700:1
Viewing Angle	70 (Left) / 70 (Right) 60 (Up) / 60 (Down)	70 (Left) / 70 (Right) 63 (Up) / 67 (Down)	70 (Left) / 70 (Right) 70 (Up) / 60 (Down)
Response Time	16ms	8ms	6ms
Input AC Voltage	AC 100–240V 60Hz/50Hz	AC 100–240V 60Hz/50Hz	AC 100–240V 60Hz/50Hz
Input DC Adaptor	DC12V / 3.15A	DC12V / 3.15A	DC12V / 5A
Input Signal	1 Vp-p Composite Video	1Vp-p Composite Video	1Vp-p Composite Video
Input Impedance	75 ohm	75 ohm	75 ohm
Operating System			
NTSC	525 Lines, 60 fields / sec.	525 Lines, 60 fields / sec.	525 Lines, 60 fields / sec.
PAL	625 Lines, 50 fields / sec.	625 Lines, 50 fields / sec.	625 Lines, 50 fields / sec.
Connector			
VGA Input	15 PIN D-SUB Connector	15 PIN D-SUB Connector	15 PIN D-SUB Connector
PC Audio Input (L/R)	Ear Phone Jack Input x 1	Ear Phone Jack Input x 1	Ear Phone Jack Input x 1
Video Input	RCA In x 1	RCA In x 1	RCA In x 1
Audio Input (L/R)	RCA In x 1 set	RCA In x 1 set	RCA In x 1 set
S-Video Input	4 PIN DIN Connector x 1	4 PIN DIN Connector x 1	4 PIN DIN Connector x 1
Speaker	1W+1W	1W+1W	2W+2W
Audio Output (L/R)	Ear Phone Jack Output x 1	Ear Phone Jack Output x 1	Ear Phone Jack Output x 1
Power Consumption	25W	35W	45W
Weight	N.W./G.W.: 4KG / 4.5KG	N.W./G.W.: 4.5 / 5.0KG	N.W./G.W.: 5KG/5.5KG
Dimension	378(W) x 191(D) x 312(H)mm	370(W) x 191(D) x 324(H)mm	419.5(W) x 191(D) x 368(H)mm
Operating Temperature	0–50°C	0–50°C	0–50°C
Storage Temperature	-20–60°C	-20–60°C	-20–60°C
Certificate	FCC CE	FCC CE	FCC CE

Specifications subject to change without notice.



For more information, please contact your nearest Elvey Security Technologies branch or Head Office on +27 (0) 11 401 6700, sales@elvey.co.za, www.elvey.co.za

